

Amendments to the Specification:

Please replace the paragraph starting on page 5, line 18 and ending on page 6, line 6 with the following amended paragraph:

Fig. 2 is a perspective view of a fan apparatus adapted to a chamber of a handler according to the present invention; and Fig. 3 is an exploded perspective view of a bearing housing as shown in Fig. 2. As illustrated therein, the fan apparatus includes: a plurality of bearing housings 60 each installed at both ends of a case 40 inside which a shaft 30 connected to a rotary central axis 11 of the rotary motor 10 by a coupling 20 is installed. One of the plurality of bearing housings 60 is provided with a second housing 61 having the bearing housing supporting the shaft 30 and a first housing 62 supporting the outer side of the second housing 61. In a case that the length of the shaft 30 is varied according to a change in temperature of the shaft 30, the second housing 61 is moved along the inner side of the first housing 62.

The following are mark-ups to show changes made to the paragraph at page 8, lines 16-24:

On the inner circumferential surface of the first housing 62, a plurality of first guide recesses 62a are formed in the direction opposite to each other. As illustrated in Figs. 4 and 5, when the second housing 61 is inserted into the first housing 62, the plurality of second guide

Serial No. 10/058,385

Docket No. MRE-0052

Amendment dated July 6, 2004

Office Action dated May 4, 2004

recesses 61a formed on the outer circumferential surface of the second housing 61 are installed with facing the plurality of first guide recesses 62a ~~facing each other~~.